



Maine Department of Transportation

Janet T. Mills
Governor

Driveway/Entrance Permit

Bruce A. Van Note
Commissioner

Permit Number: 39510 - Entrance ID: 1

LOCATION

OWNER

Name: **DPC, LLC**
 Address: **P.O. Box 177
 Naples, ME 04055**
 Telephone: **(207)897-6752**

Route: **0302X, Roosevelt Trail**
 Municipality: **Naples**
 County: **Cumberland**
 Tax Map: **U02 Lot Number: 24**
 Culvert Size: **18 inches**
 Culvert Type: **plastic**
 Culvert Length: **100 feet**
 Date of Permit: **July 12, 2024**
 Approved Entrance Width: **26 feet**

Date Printed: **July 12, 2024**

In accordance with rules promulgated under 23 M.R.S.A., Chapter 13, Subchapter I, Section 704, the Maine Department of Transportation (MaineDOT) approves a permit and grants permission to perform the necessary grading to construct, in accordance with sketch or attached plan, **an Entrance to Dollar General Retail Store** at a point **450 feet East** from **Harrison Road**, subject to the Chapter 299 Highway Driveway and Entrance Rules, standard conditions and special conditions (if any) listed below.

Conditions of Approval:

This Permittee acknowledges and agrees to comply with the Standard Conditions and Approval attached hereto and to any Specific Conditions of Approval shown here.

(G = GPS Location; W = Waiver; S = Special Condition)

G - THE ENTRANCE SHALL BE LOCATED AT GPS COORDINATES: 43.969510N, -70.592631W.


S - In the town of Naples on the southwesterly side of Route 302, the centerline being approximately 450 feet southeasterly of the centerline of Harrison Road/RTE 35 and approximately 76 feet northwesterly of utility pole 22.

S - This permit approves the entrance for up to 99 one-way vehicle trips in the peak hour. When a change of use occurs, the Property Owner will be required to gain the approval of the MaineDOT so as to evaluate the one-way vehicle trips in the peak hour. If at any time it is determined that the change of use results in one-way vehicle trips in the peak hour exceeding the 99 trip threshold, the MaineDOT may require the owner to apply for a Traffic Movement Permit.

S - The entrance shall be constructed as shown on the plan titled "Naples Dollar General" page C2.0 drawn by Main-Land Development Consultants, Inc. with a date of May 15, 2024.

S - This access is limited to the approved use. Any change in the use of this access will require additional Permit approval.

S - THE SIDEWALK MUST BE RECONSTRUCTED TO MEET MaineDOT & THE TOWN OF NAPLES STANDARDS.

Approved by:  Date: 7-12-2024

STANDARD CONDITIONS AND APPROVAL

1. Provide, erect and maintain all necessary barricades, lights, warning signs and other devices as directed by MaineDOT to properly safeguard traffic while the construction is in progress.
2. At no time cause the highway to be closed to traffic
3. Where the driveway is located within a curb, curb and gutter, and/or sidewalk section, completely remove the existing curb, curb and gutter, and/or sidewalk as may be required to create the driveway and restore drainage. All driveways abutting sidewalk sections shall meet the requirements set forth in the Americans with Disabilities Act of 1990, 42 U.S.C. Sec. 12131 et seq.
4. Obtain, have delivered to the site, and install any culverts and/or drainage structures which may be necessary for drainage, the size, type and length as called for in the permit pursuant to 23 M.R.S.A. Sec. 705. All culverts and/or drainage structures shall be new.
5. Start construction of the proposed driveway within twenty-four (24) months of the date of permit issuance and substantially complete construction of the proposed driveway within twelve months of commencement of construction.
6. Comply with all applicable federal, state and municipal regulations and ordinances.
7. Do not alter, without the express written consent of the MaineDOT, any culverts or drainage swales within the MaineDOT right of way.
8. File a copy of the approved driveway permit with the affected municipality or LURC, as appropriate within 5 business days of receiving the MaineDOT approval.
9. Construct and maintain the driveway side slopes to be no steeper than the adjacent roadway side slopes, but in no case to be steeper than 3 horizontal to 1 vertical, unless the side slope is behind existing roadway guardrail, in which case it shall be no steeper than 2 horizontal to 1 vertical.
10. Notify the MaineDOT of a proposed change of use served by the driveway when increase in traffic flow is expected to occur. This does not exempt the need for obtaining a Traffic Movement Permit (TMP) if trip generation meets or exceeds 100 passenger car equivalents (PCE) during the peak hour of the day.
11. Construct or implement and maintain erosion and sedimentation measures sufficient to protect MaineDOT facilities.
12. Driveways shall be designed such that all maneuvering and parking of any vehicles will take place outside the highway right-of-way and where vehicles will exit the premises without backing onto the highway traveled way or shoulders. All driveways will have a turnaround area to accommodate vehicles using the premises.
13. Closing any portion of a highway or roadway including lanes, shoulders, sidewalks, bike lanes, or ATV access routes is not permitted without MaineDOT approval.


FURTHER CONDITION OF THE PERMIT

The owner shall assume, the defense of, and pay all damages, fines, and penalties for which he/she shall become liable, and shall indemnify and safe harmless said Department, its representatives, agents and employees from liability, actions against all suits, claims, damages for wrongful death, personal injuries or property damage suffered by any person or association which results from the willful or negligent action or inaction of the owner/applicant (agent) and in proceedings of every kind arising out of the construction and maintenance of said entrance(s), including snow removal.

Nothing herein shall, nor is intended to, waive any defense, immunity or limitation of liability which may be available to the MaineDOT, their officers, agents or employees under the Maine Tort Claims Act or any other privileges and/or immunities provided by law. It is a further condition that the owner will agree to keep the right of way inviolate for public highway purposes and no signs (other than traffic signs and signals), posters, billboards, roadside stands, culvert end walls or private installations shall be permitted within Right of Way limits.

F.H.V.A. REG. NO.	STATE	PROJECT NUMBER	SHEET NO.	TOTAL SHEET
1	MAINE			

ENTRANCES WITH HIGH NUMBER OF TRUCK MOVEMENTS
MAY BE DESIGNED ON AN INDIVIDUAL BASIS




GRAVEL ENTRANCE

PAVED ENTRANCE

① ENTRANCE ANGLE SHOULD NOT BE LESS THAN 45°


COMMERCIAL/INDUSTRIAL ENTRANCE
ONTO UNCURBED HIGHWAY
(PAVED SHOULDERS)

EN004



State of Maine
 Department of Transportation
Entrance / Driveway Details

PLAN




GENERAL NOTES -


1. ALL RESIDENTAL OR COMMERCIAL DRIVES WITH 10% GRADE OR MORE SLOPING DOWN TOWARDS THE HIGHWAY SHALL BE PAVED TO THE RIGHT OF WAY LINE, AS A MINIMUM, INCLUDING SHOULDER, IF GRAVEL AND HAVE DITCHES TO CONTROL RUNOFF.
2. DRIVES SLOPING TO THE HIGHWAY SHALL BE CROWNED (1/2" PER FT. MINIMUM).
3. TO THE MAXIMUM EXTENT PRACTICAL, THE ENTRANCE MUST BE CONSTRUCTED PERPENDICULAR TO THE HIGHWAY AT THE POINT OF ACCESS. EXCEPT WHERE CURBING EXISTS OR IS PROPOSED, THE MINIMUM RADIUS ON THE EDGES OF THE ENTRANCE MUST BE 10 FEET OR AS OTHERWISE REQUIRED AS SHOWN.
4. ENTRANCES/DRIVEWAYS WILL BE BUILT WITH AN ADEQUATE TURN-AROUND AREA ON SITE TO ALLOW ALL VEHICLES TO MANUEVER AND PARK WITHOUT BACKING ONTO THE HIGHWAY. THIS TURN-AROUND SHALL BE AT LEAST 8 FEET WIDE BY 15 FEET LONG.
5. ENTRANCES/DRIVEWAYS AND OTHER ASSOCIATED SITE WORK WHICH DIRECTS WATER (RUNOFF) TOWARD THE HIGHWAY MUST BE CONSTRUCTED, CROWNED STABILIZED AND MAINTAINED WITH MATERIALS AND APPROPRIATE TEMPORARY/PERMANENT EROSION CONTROL MATERIALS IN ACCORDANCE WITH MDOT BEST MANAGEMENT PRACTICES.
6. THE PROFILE OF THE ENTRANCES MUST COMPLY WITH THE DETAILS SHOWN ON PAGE 2.

MDOT Entrance / Driveway Details, Continued

PROFILE Details



NOTE :
 Grade of Existing Shoulder Should Be Maintained To Create A Gutter
 With a Minimum Of Three Inches Below The Edge Of Traveled Way.
 * Distance Of The Gutter From The Edge Of Traveled Way Should Be
 The Same As Existing Shoulder Or A Minimum Of 4 Feet.



Driveway Cross Section

